





POWERFUL, MINI, TISSUE HOMOGENIZER



The MiniG[™] is the ideal solution for labs that want the power of the 2010 Geno/Grinder[°] with a lower sample throughput. It was created for applications involving sample preparation for DNA/RNA and protein extractions as well as pesticide residue analysis.

TYPICAL SAMPLES

Plant and animal tissue, cell cultures, seeds, yeast, leaves and bacteria.

FEATURES

- : Vigorous clamp movement results in increased yields.
- : Consistent vertical motion of the clamp ensures equal conditions for all samples.
- : Kryo-Tech[®] accessories are available to preserve temperature sensitive samples.
- Light & portable with a small footprint that minimizes bench space.

SPEX[®] SamplePrep **?**

www.spexsampleprep.com

SPEX[°]SamplePrep **?**



1600 MiniG[™]

Specifications

- 1. Window in lid allows you to see the grinding process.
- 2. Lid has a safety interlock switch that stops the motor if the lid is opened during the grinding process.
- 3. Easy-to-use clamp keeps samples secure during the shaking process.
- 4. Clamp typically holds up to 2 titer plates or 48 x 2 mL vials when stacked.
- 5. LCD display screen shows run times in minute: second format.
- 6. Rate and timer controls allow you to adjust speed and set time.
- 7. Start and stop buttons allow you to start and stop the grinding process.

Voltage	115V/60Hz or 230V/50Hz	Power Cord	3-prong grounded plug 115V / 60Hz. 2-prong European cord for 230V / 50Hz.
CE Approved	Yes		
Dimensions	21.5 in. (54.6 cm) high x 11.25 in. (28.6 cm) wide x 17.0 in. (43.2 cm)deep	Clamp Movement	1.25 in. (3.2 cm) vertical
Weight	40 lbs. (22 kg)	Clamp Speed	Adjustable from 500 to 1500 strokes/minute
Motor	1/7 HP	Timer/Controls	Digital display in minutes & seconds, maximum 10:00

Corporate Headquarters

SPEX SamplePrep 15 Liberty Street Metuchen, NJ 08840 1-855-GET-SPEX Tel: 732-623-0465 Fax: 732-906-2492 sampleprep@spex.com www.spexsampleprep.com



SPEX is proudly represented in Australia by AXT Pty. Ltd. 1/3 Vuko Pl., Warriewood NSW 2102 Australia T. +61 (0)2 9450 1359 F. +61 (0)2 9450 1365 W. www.axt.com.au E. info@axt.com.au

